

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Rust Patrol®: Incorrutable (Rust Patrol®: Heavy Duty)  
 Product form : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Rust and corrosion inhibitor, Water-displacing agent. Lubricant. Penetrating fluid. Shake before use.

#### 1.3. Details of the supplier of the safety data sheet

A-76 Technologies, Inc. DBA Aidant Brands  
 5151 Mitchelldale Street, #B4  
 Houston, TX 77092  
 713.400.3100  
 www.rustpatrol.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Aerosol 2 H223  
 Asp. Tox. 1 H304

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H223 - Flammable aerosol  
 H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 P211 - Do not spray on an open flame or other ignition source  
 P251 - Pressurized container: Do not pierce or burn, even after use  
 P301+P310 - IF SWALLOWED: Immediately call poison center/doctor/...  
 P331 - Do NOT induce vomiting  
 P405 - Store locked up  
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
 P501 - Dispose of contents/container to ...

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	10 - 30*
Carbon Dioxide (as compressed gas)	(CAS No) 124-38-9	1 - 5*

\*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

# Rust Patrol®: Heavy Duty Aerosolized

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May be fatal if swallowed and enters airways.
- Symptoms/effects after inhalation : May be fatal if swallowed and enters airways.
- Symptoms/effects after skin contact : May cause skin irritation.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : May cause gastrointestinal irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.
- Unsuitable extinguishing media : Water.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol.
- Explosion hazard : Product is not explosive.
- Reactivity : No data available.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

#### 6.4. Reference to other sections

No additional information available

# Rust Patrol®: Heavy Duty Aerosolized

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe vapors and mists. Keep away from sources of ignition - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Heat sources. Keep container closed when not in use.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Carbon Dioxide (as compressed gas) (124-38-9)</b>	
ACGIH TWA (ppm)	5000 ppm
ACGIH STEL (ppm)	30000 ppm
Remark (ACGIH)	asphyxia
OSHA PEL (TWA) (mg/m <sup>3</sup> )	9000
OSHA PEL (TWA) (ppm)	5000
OSHA PEL (STEL) (mg/m <sup>3</sup> )	54000 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	30000

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas.  
Personal protective equipment : Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear suitable protective clothing. Wear long sleeves.

Respiratory protection : Where excessive vapor, mist, or dust may result, use NIOSH approved respiratory protection equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : No data available  
Odor : No data available  
Odor Threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 45 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available

# Rust Patrol®: Heavy Duty Aerosolized

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: 0.2 psi
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.6 - 8 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

No data available.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

No data available.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

No data available.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h

Carbon Dioxide (as compressed gas) (124-38-9)	
LD50 oral rat	study technically not feasible
LD50 dermal rat	study technically not feasible
LC50 inhalation rat (mg/l)	not classified

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May be fatal if swallowed and enters airways.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.

# Rust Patrol®: Heavy Duty Aerosolized

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1950 Aerosols, 2.1
- UN-No.(DOT) : 1950
- DOT NA no. : UN1950
- Proper Shipping Name (DOT) : Aerosols
- Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Quantity Limitations Passenger aircraft/rail : 75 kg  
(49 CFR 173.27)
- DOT Quantity Limitations Cargo aircraft only (49 : 150 kg  
CFR 175.75)
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

- Emergency Response Guide (ERG) Number : 126
- Other information : No supplementary information available.

#### Transport by sea

- UN-No. (IMDG) : 1950
- Proper Shipping Name (IMDG) : AEROSOLS
- Class (IMDG) : 2 - Gases

#### Air transport

- UN-No. (IATA) : 1950
- Proper Shipping Name (IATA) : Aerosols, flammable
- Class (IATA) : 2

# Rust Patrol®: Heavy Duty Aerosolized

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Rust Patrol®: Incorrutable (Rust Patrol®: Heavy Duty)

All chemical substances in this product are listed in the EPA (Environmental Protection Agency) TSCA (Toxic Substances Control Act) Inventory

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
-------------------------------------	--

#### 15.2. International regulations

No additional information available.

#### 15.3. US State regulations

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

##### Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

U.S. - Massachusetts - Right To Know List

##### Dimethyl sulfoxide (67-68-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

##### Carbon Dioxide (as compressed gas) (124-38-9)


U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.  
Revision date : 10/31/2017  
Other information : Author: MDT.

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.  
NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



#### HMIS III Rating

Health : 3\*  
Flammability : 3  
Physical : 0  
Personal protection :

To the best of our knowledge, the information contained herein is accurate. However, A-76 Technologies, Inc. DBA Aidant Brands, nor any of its distributors assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.